



Vibration

1- Vibration analysis of carbon nanotube-reinforced composite microbeams

By:

[Civalek, O](#) (Civalek, Omer) [1]; [Dastjerdi, S](#) (Dastjerdi, Shahriar) [2], [3]; [Akbas, SD](#) (Akbas, Seref D.) [4]; [Akgoz, B](#) (Akgoz, Bekir) [3]

(provided by Clarivate)

DOI

10.1002/mma.7069

Early Access

JAN 2021

Indexed

2021-01-20

Document Type

Article; Early Access

Abstract

In the present article, free vibration behavior of carbon nanotube-reinforced composite (CNTRC) microbeams is investigated. Carbon nanotubes (CNTs) are distributed in a polymeric matrix with four different patterns of the reinforcement. The material properties of the CNTRC microbeams are predicted by using the rule of mixture. The microstructure-dependent governing differential equations are derived by applying Hamilton's principle on the basis of couple stress theory and several beam theories. The obtained vibration equation is solved by using Navier's solution method. The effects of length scale parameter, length/thickness ratio, volume fraction and the reinforcement pattern of CNTs on frequencies are examined. It is observed that the biggest frequencies occur in X-Beam while O-Beam has the lowest ones. It is also found that the size effect is more prominent when the thickness of the beam is close to the length scale parameter and this effect nearly disappears as the thickness of the beam increases.

Keywords

Author Keywords

[beam theories](#)[carbon nanotube](#)[reinforced beams](#)[size effect](#)[vibration](#)

Keywords Plus

[STRAIN GRADIENT THEORY](#)[PULL-IN INSTABILITY](#)[MECHANICAL-PROPERTIES](#)[CYLINDRICAL-SHELLS](#)[SHEAR DEFORMATION](#)[BUCKLING ANALYSIS](#)[THERMOMECHANICAL RESPONSE](#)[NONLOCAL ELASTICITY](#)[NONLINEAR RESPONSE](#)[SANDWICH PLATES](#)



Vibration

2- Review of ultrasonic vibration-assisted machining in advanced materials

By:

[Yang, ZC](#) (Yang, Zhichao) [1]; [Zhu, LD](#) (Zhu, Lida) [1]; [Zhang, GX](#) (Zhang, Guixiang) [2]; [Ni, CB](#) (Ni, Chenbing) [1]; [Lin, B](#) (Lin, Bin) [3]

(provided by Clarivate)

Volume

156

Article Number

103594

DOI

10.1016/j.ijmachtools.2020.103594

Published

SEP 2020

Indexed

2020-09-22

Document Type

Review

Abstract

Compared to conventional machining (CM), ultrasonic vibration-assisted machining (UVAM) with high-frequency and small-amplitude has exhibited good cutting performances for advanced materials. In recent years, advances in ultrasonic generator, ultrasonic transducer, and horn structures have led to the rapid progress in the development of UVAM. Following this trend, numerous new design requirements and theoretical concepts have been proposed and studied successively, however, very few studies have been conducted from a comprehensive perspective. To address this gap in the literature and understanding the development trend of UVAM, a critical overview of UVAM is presented in this study, covering different vibration-assisted machining styles, device architectures, and theoretical analysis. This overview covers the evolution of typical hardware systems used to achieve vibratory motions from the one-dimensional UVAM to three-dimensional UVAM, the discussion of cutting characteristics with periodic separation between the tools and workpiece and the analysis of processing properties. Challenges for UVAM include ultrasonic vibration systems with high power, large amplitude, and high efficiency, as well as theoretical research on the dynamics and cutting characteristics of UVAM. Consequently, based on the current limitations and challenges, device improvement and theoretical breakthrough play a significant role in future research on UVAM.

Keywords

Author Keywords

[Ultrasonic vibration-assisted machining](#)[Advanced materials](#)[Cutting characteristics](#)[Ultrasonic vibration system](#)



Vibration

Keywords Plus

MATERIAL REMOVAL MECHANISM TEXTURED SURFACE GENERATION BRITTLE-DUCTILE TRANSITION WORKPIECE CONTACT RATES SUBSURFACE DAMAGE MONOCRYSTAL SAPPHIRE RESIDUAL-STRESS CFRP COMPOSITE TITANIUM-ALLOY GRINDING EUAG



Vibration

3- Dynamical Modeling and Boundary Vibration Control of a Rigid-Flexible Wing System

By:

[He, W](#) (He, Wei) [\[1\]](#), [\[2\]](#); [Wang, TT](#) (Wang, Tingting) [\[1\]](#), [\[2\]](#); [He, XY](#) (He, Xiuyu) [\[1\]](#), [\[3\]](#), [\[4\]](#); [Yang, LJ](#) (Yang, Lung-Jieh) [\[5\]](#); [Kaynak, O](#) (Kaynak, Okayay) [\[6\]](#), [\[7\]](#)

(provided by Clarivate)

Volume

25

Issue

6

Page

2711-2721

DOI

10.1109/TMECH.2020.2987963

Published

DEC 2020

Indexed

2021-01-05

Document Type

Article

Abstract

A boundary control approach is used to control a two-link rigid-flexible wing in this article. Its design is based on the principle of bionics to improve the mobility and the flexibility of aircraft. First, a series of partial differential equations (PDEs) and ordinary differential equations (ODEs) are derived through the Hamilton's principle. These PDEs and ODEs describe the governing equations and the boundary conditions of the system, respectively. Then, a control strategy is developed to achieve the objectives including restraining the vibrations in bending and twisting deflections of the flexible link of the wing and achieving the desired angular position of the wing. By using Lyapunov's direct method, the wing system is proven to be stable. The numerical simulations are carried out with the finite difference method to prove the effectiveness of designed boundary controllers.

Keywords

Author Keywords

[Vibrations](#)[IEEE transactions](#)[Mechatronics](#)[Biomimetics](#)[Mathematical model](#)[Strain Actuators](#)[Boundary control](#)[distributed parameter system](#)[rigid-flexible coupled wing](#)[vibration control](#)

Keywords Plus

[EULER-BERNOULLI BEAM](#)[ACTIVE DISTURBANCE](#)[TRACKING CONTROL](#)[WAVE-EQUATION](#)[STABILIZATION](#)[ROBOT](#)[PDE](#)[MANIPULATORS](#)[PERFORMANCE](#)[REJECTION](#)



Vibration

4- Study on Three-Dimensional Dynamic Stability of Open-Pit High Slope under Blasting Vibration

By:

[Li, XS](#) (Li, Xiaoshuang) [\[1\]](#), [\[2\]](#), [\[3\]](#); [Li, QH](#) (Li, Qihang) [\[4\]](#); [Hu, YJ](#) (Hu, Yunjin) [\[1\]](#); [Chen, QS](#) (Chen, Qiusong) [\[5\]](#); [Peng, J](#) (Peng, Jun) [\[2\]](#); [Xie, YL](#) (Xie, Yulin) [\[4\]](#); [Wang, JW](#) (Wang, Jiawen) [\[4\]](#)

(provided by Clarivate)

Volume

2021

Special Issue

4

Article Number

6426550

DOI

10.2113/2022/6426550

Published

JUL 2021

Indexed

2022-03-31

Document Type

Article

Abstract

The propagation process of blasting vibration has always been a difficult problem affecting the stability of high slopes in open-pit mines. Taking the Jianshan Phosphorus Mine as the research background, combined with engineering geological investigation, field blasting test, blasting vibration monitoring, numerical simulation technology, and theoretical analysis, the three-dimensional dynamic stability of the adjacent high slope after blasting vibration was systematically studied. In our study, a small-diameter buffer shock-absorbing blasting technology near the slope was proposed, which greatly improved the production efficiency. Through regression analysis of a large amount of vibration test data, the law of blasting vibration propagation in Jianshan stope and Haifeng stope was obtained. In addition, by establishing four three-dimensional geomechanical numerical models, the slope's own frequency, damping characteristics, and dynamic response acceleration distribution after detonation were studied, respectively. On the other hand, under the action of Ei Centro wave with 8-degree seismic intensity, the maximum total acceleration and maximum total displacement of the slope were calculated and analyzed. Both the explosion unloading of the 8-degree earthquake and the Ei Centro wave simulation results showed that the high slope near the Jianshan Phosphorus Mine was generally in a stable state. Thus, this study can provide technical support and theoretical guidance for mine blasting.

Keywords



Vibration

Keywords Plus

[NUMERICAL-SIMULATIONPROPAGATIONBEHAVIORFAILUREDRIVEN](#)



Vibration

5- On the modelling of the vibration behaviors via discrete singular convolution method for a high-order sector annular system

By:

[Liu, Y](#) (Liu, Yue) [1]; [Wang, WQ](#) (Wang, Wanqiu) [2]; [He, T](#) (He, Tao) [3]; [Moradi, Z](#) (Moradi, Zohre) [4]; [Benitez, MLA](#) (Larco Benitez, Myrian A.) [5]

(provided by Clarivate)

DOI

10.1007/s00366-021-01454-z

Early Access

JUL 2021

Indexed

2021-08-10

Document Type

Article; Early Access

Abstract

This research presents a numerical investigation on the dynamic information of the axisymmetric sandwich annular sector plate via a higher-order continuum elasticity theory. The sandwich annular sector plate comprises multi-hybrid nanocomposite reinforced (MHCR) face sheets in the top, bottom layers, and a honeycomb core. For modeling the thermal situation and the thickness of the structure, three-kinds of thermal loading are presented. For simulating MHCR face sheets, the role of the mixture and Halpin-Tsai micromechanics model is utilized. For obtaining the governing equations and various boundary conditions, first-order shear deformation theory (FSDT), as well as Hamilton's principle, are presented. For solving the equations and obtaining eigenvalue, and eigenvector of the current structure, discrete singular convolution method (DSCM) as a numerical one is investigated. Consequently, a parametric study is carried out to examine the impacts of honeycomb network angle, thickness to length ratio of the honeycomb, honeycomb to face sheet thickness ratio, fibers angle, outer to inner radius ratio, and weight fraction of CNTs on the dynamics of the current sandwich structure. The results show that for clamped edge and each $t(h)/l(h)$, increasing $\theta(h)/\pi$ is a reason for decreasing the natural frequency of the disk. Another consequence is that the impact of temperature changes on the frequency of the disk is hardly dependent on the fiber angle. It means that the effect of temperature changes on the frequencies of the current system is more considerable at $0.2 \leq \theta(f)/\pi \leq 0.4$ and $0.6 \leq \theta(f)/\pi \leq 0.8$.

Keywords

Author Keywords

[Annular sector sandwich plate](#)[Discrete singular convolution method](#)[Honeycomb core](#)[Halpin-Tsai micromechanics model](#)[Thermal situation](#)



Vibration

Keywords Plus

[STRENGTH PREDICTION](#)[COMPOSITE BEAMS](#)[SHEAR-](#)

[STRENGTH](#)[CARBON IMPERFECTION](#)[OPTIMIZATION](#)[SENSITIVITY](#)[AMPLITUDE](#)[ALGORITHM](#)[SENSOR](#)



Vibration

6- Enhancing active vibration control performances in a smart rotary sandwich thick nanostructure conveying viscous fluid flow by a PD controller

By:

[Zhang, Y](#) (Zhang, Yu) [1]; [Wang, ZY](#) (Wang, Zeyu) [2]; [Tazeddinova, D](#) (Tazeddinova, Diana) [3], [4]; [Ebrahimi, F](#) (Ebrahimi, Farzad) [5]; [Habibi, M](#) (Habibi, Mostafa) [6], [7], [8]; [Safarpour, H](#) (Safarpour, Hamed) [5]

(provided by Clarivate)

DOI

10.1080/17455030.2021.1948627

Early Access

JUL 2021

Indexed

2021-07-13

Document Type

Article; Early Access

Abstract

This is the first research on the smart control and frequency analysis of a cylindrical sandwich nanoshell in the framework of the numerical-based generalized differential quadrature method (2D-GDQM). The current sandwich smart nanostructure is made of a honeycomb core and piezoelectric face sheets as sensor and actuator (PFSA). For modeling the size-dependent nanoshell, nonlocal stress-strain gradient theory (NSGT) is presented. Also, this nanostructure is under conveying viscous fluid, and the related force is calculated by the modified formulation of Navier-Stokes. Also, the current structure rotates around its axial direction. The stresses and strains are obtained using the higher-order shear deformation theory (HSDT). The external voltage is applied to the sensor layer, and a Proportional-Derivative (PD) controller is used for sensor output control. Governing equations and boundary conditions of the cylindrical sandwich nanoshell are obtained by implementing Hamilton's principle. The results show that the geometry of honeycomb core, PD controller, velocity of fluid flow, length to radius ratio (L/R), and applied voltage and have a significant influence on the frequency characteristics of a cylindrical sandwich nanoshell. Another important consequence is that applying the PD controller leads to an increase in the critical velocity of fluid flow in the smart nanostructure.

Keywords

Author Keywords

[Sensor and actuator](#)[fluid flow](#)[PD controller](#)[Navier-Stokes equations](#)[nanostructure](#)[honeycomb core](#)[NSGT](#)

Keywords Plus

[SPRING-MASS SYSTEM](#)[CYLINDRICAL PANELS](#)[BEHAVIOR](#)[SHELL](#)[BEAM](#)[EFFICACY](#)[SAFETY](#)[SENSOR](#)